

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 March 2001 (08.03.2001)

PCT

(10) International Publication Number
WO 01/16854 A2

(51) International Patent Classification⁷: G06F 19/00

(21) International Application Number: PCT/US00/20356

(22) International Filing Date: 25 July 2000 (25.07.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/387,041 31 August 1999 (31.08.1999) US
09/387,043 31 August 1999 (31.08.1999) US

(71) Applicant: AIR ADVICE.COM [US/US]; 1727 S.E. 43rd Street, Portland, OR 97215 (US).

(72) Inventor: SKARDON, John, N.; 14413 N.E. 26th Avenue, Vancouver, WA 98686 (US).

(74) Agents: AUYEUNG, Aloysius, T., C. et al.; Blakely, Sokoloff, Taylor & Zafman, 12400 Wilshire Boulevard, 7th floor, Los Angeles, CA 90025-1026 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— Without international search report and to be republished upon receipt of that report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ALLERGEN DETECTION AND AIR/ASTHMA ADVICE PROVISION



(57) Abstract: A novel air/asthma advice method and apparatus for providing air/asthma advice to an asthma patient, taking into consideration indoor allergen as well as outdoor air quality conditions, is disclosed. Allergen data (preferably for allergen with sizes smaller than 5 microns) for an indoor location (where the asthma patient is situated) are collected, and provided to a geographically removed air/asthma advice server. The server, in turn, retrieves air quality data for a surrounding outdoor area of the indoor location (from either a private or an independent source), and generates an allergen advice response for the asthma patient. The air/asthma advice is generated based at least in part on the received allergen data and the retrieved air quality data. The air/asthma advice may be delivered to the asthma patient in any one of a number of forms (a beeping alert, a pager, fax, email or voice message, and so forth). Various other alterations and modifications under different embodiments are also disclosed.

WO 01/16854 A2

Allergen Detection And Air/Asthma Advice Provision

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to the field of medical devices and advising systems. More specifically, the present invention relates to allergen detection and air or asthma related advising systems.

2. Background Information

Asthma is a chronic disease that affects among other things, the lung functions of a patient. It is estimated that 6% to 9% of the population of the developed world are affected, and the number of diagnosed cases is growing at 5% per year, ten times the rate of population growth. The number of newly diagnosed cases of pediatric asthma has the health authorities of many countries consider asthma to be an epidemic. In United States, about 15 millions American are affected, making it the sixth ranked chronic disease of the country. About 5,500 people die from asthma related complication each year. The annual medical cost is estimated to be \$6 billion. In addition, thousands of work and school days are lost.

Lung irritants such as particulates, plants and animal allergens, and certain types of man-made pollution are the usual triggers leading to asthma attacks. Typically, they are 50 microns or smaller. In the home setting, recent research has determined that allergens can accumulate to levels 2x – 10x higher than outside levels. More importantly, "respirable" particulates less than 5 microns in size are of particular concern to health authorities. Current asthma treatment guidelines typically advise a patient to, in order of priority, (1) prevent an attack by avoiding asthma triggers, (2) check their lung function regularly and (3) take medication when necessary.

Although prevention is a high priority or even preferred aspect of the treatment plan for a patient, currently, very limited help is available to assist a patient to avoid asthma triggers, especially in the home setting. This is because allergenic particles that are 50 microns or smaller in size are too small to see without a microscope. Much of the air monitoring devices known in the art are catered for commercial (i.e. workplace) use, designed to monitor industrial pollutants. U.S. patents 5,001,463 and 5,646,597 issued to Hamburger disclosed two allergen detection devices for triggering an alarm when allergen level exceeding certain predetermined threshold is detected. A filter, collection and detection arrangement is employed in the '463 patent, whereas the '597 patent improves on the optical detection of the '463 patent. However, both devices suffer from at least the following disadvantages:

- (a) neither devices are designed to detect respirable allergens that are smaller than 5 microns, which as mentioned above, have recently been identified by medical research as among the most relevant allergens to avoid;
- (b) both devices are only capable of generating an alarm based on the amount of allergens detected in the ambient air of the location of the monitoring device, which when located indoor, ignore the critical component of outdoor air quality (i.e. the air quality of the immediate outdoor area surrounding the indoor location);
- (c) the vertical sampling arrangement requires the use of extensive filtering and purging system;
- (d) the art ignores the role of humidity and temperature in the lung function;
- (e) maintaining, including cleaning, and calibrating these devices are difficult, requiring extensive disassembly and instrumentation; and
- (f) no provisions are provided for storing and communicating the collected data.

Thus, an improved approach to allergen monitoring and air/asthma advice generation is desired.

3. Terminology

Throughout the remaining specification, including the claims, usage of the term "allergen" is intended to include particulates, plants and animal allergens, man-made pollution, and the like, and usage of the term "air/asthma advice" is intended to cover air quality and/or asthma related information, suggestion, counsel, guidance, recommendation, admonition, direction, instruction, alert, warning, and the like.

SUMMARY OF THE INVENTION

Allergen data (preferably for allergen with sizes smaller than 5 micron) for a location (where the asthma patient is situated) are collected, and provided to a geographically removed air/asthma advice server. The server, in turn, retrieves air quality data for a surrounding area of the location (from either a private or an independent source), and generates an air/asthma advice response for the asthma patient. The air/asthma advice is generated based at least in part on the received allergen data and the retrieved air quality data. Under various embodiments, the air/asthma advice is delivered to the asthma patient in one or more of a number of forms, a beeping alert, a pager, fax, email or voice message, and so forth.

BRIEF DESCRIPTION OF DRAWINGS

The present invention will be described by way of exemplary embodiments, but not limitations, illustrated in the accompanying drawings in which like references denote similar elements, and in which:

Figure 1 illustrates an overview of the present invention in accordance with one embodiment;

Figures 2a-2b illustrate allergen detection arrangement of **Fig. 1** in further detail, in accordance with two embodiments;

Figures 3a-3e illustrate air/asthma advice receipt arrangement of **Fig. 1** in further detail, in accordance with two embodiments;

Figure 4 illustrates an example server suitable for use to practice air/asthma advice server of **Fig. 1**, in accordance with one embodiment;

Figure 5 illustrates the air/asthma advice application of **Fig. 1** in further detail, in accordance with one embodiment;

Figure 6 illustrates the patient client database of **Fig. 1** in further detail, in accordance with one embodiment; and

Figure 7 illustrates an air/asthma advice method of the present invention, in accordance with one embodiment.

DETAILED DESCRIPTION OF THE INVENTION

In the following description, various aspects of the present invention will be described, and various details will be set forth in order to provide a thorough understanding of the present invention. However, it will be apparent to those skilled in the art that the present invention may be practiced with only some or all aspects of the present invention, and the present invention may be practiced without the specific details. In other instances, well known features are omitted or simplified in order not to obscure the present invention.

Parts of the description will be presented using terminology commonly employed by those skilled in the art to convey the substance of their work to others skilled in the art, including terms of operations performed by a computer system, and their operands, such as transmitting, receiving, retrieving, determining, generating, allergen data, air quality data, and the like. As well understood by those skilled in the art, these operands take the form of electrical, magnetic, or optical signals, and the operations involve storing, transferring, combining, and otherwise manipulating the signals through electrical, magnetic

or optical components of a system. The term system includes general purpose as well as special purpose arrangements of these components, that are standalone, adjunct or embedded.

Various operations will be described as multiple discrete steps performed in turn in a manner that is most helpful in understanding the present invention. However, the order of description should not be construed as to imply that these operations are necessarily performed in the order they are presented, or even order dependent. Lastly, repeated usage of the phrase "in one embodiment" does not necessarily refer to the same embodiment, although it may.

Referring now **Figure 1**, wherein a block diagram illustrating an overview of the present invention in accordance with one embodiment is shown. As illustrated, for the particular embodiment, each patient client **102** is equipped with allergen detection arrangement **104**, as well as air/asthma advice receipt arrangement **106**. Both allergen detection and air/asthma advice receipt arrangements **104** and **106** are communicatively coupled to geographically removed air/asthma advice server **112**; for the particular embodiment, through communication links **108** and **110** respectively. Air/asthma server **112** includes air/asthma advice application **114** and patient client database **116**. Air/asthma advice server **112** in turn is also communicatively coupled to a number of other remote servers **122**, through a communication link or links **118**. Each of the other remote servers **122** includes at least air quality and other asthma related information databases **124**.

Allergen detection arrangement **104** provided to each patient client **102** is used to detect allergen level at a location for the patient client **102**, the location the particular arrangement **104** is located. In a presently preferred embodiment, to be described more fully below, the allergens monitored are allergens with sizes smaller than 5 micron. Typically, a monitored location is a "fixed" indoor location, such as the "home" or the office of a patient client **102**.

The term "home" as used herein is intended to cover the primary as well as other temporary residence of a patient client **102**, where the patient client **102** e.g. is an "invitee", such as someone else's home, a hotel, and so forth. As will be readily apparent from the description to follow, in alternate embodiments, a monitored location may also be simply a "substantially stationery" enclosed location, such as the patient client's automobile or a boat, to be described more fully below.

In accordance with the present invention, allergen detection arrangement **104** provides the detected allergen level at a monitored location to air/asthma server **112**, more specifically, to air/asthma advice application **114** of server **112**.

In response, air/asthma advice application **114** retrieves at least air quality data for a general area of the location monitored, e.g. in the earlier described case of a "fixed" indoor location, an outdoor area surrounding the indoor location being monitored. For the particular embodiment, air/asthma advice application **114** retrieves the air quality data from remote servers **122**. Examples of air quality data include air pollution data (such as ozone, oxides of nitrogen, oxides of sulphur, photochemical smog), weather data (such as humidity, temperature, and barometric pressure), natural phenomena (such as pollen level, occurrence of sandstorm, tornado, forest fire,), man made pollution events (such as agricultural burns) and so forth. Examples of remote servers **122** include publicly accessible servers of the Environmental Protection Agency (EPA) and National Weather Services of the United States Government, as well as network or cable news web servers, such as MSNBC.com and CNN.com. In alternate embodiments, air/asthma advice application **114** may further retrieve other asthma related information for the general area from additional other remote servers **122**. Examples of other asthma related information and additional other servers **122** include asthma alerts or warning bulletins posted on free or subscription based servers of educational and research institutions of the like (such as servers of the

National Center for Diseases, Harvard Medical School and so forth). In yet other alternate embodiments, air/asthma advice application **114** may cache some of the air quality and other asthma related data (e.g. the most frequently accessed data) on server **112**, i.e. maintaining local copies of the data. For these embodiments, whenever local copies are available, air/asthma advice application **114** may retrieve from the local cache instead.

The size of the general area is dependent on the granularity of the air quality and other asthma related data being maintained by other servers **122**. For examples, the size of the general area may be an area covered by the same zip code, or it may be an entire statistical metropolitan area, depending on whether the air quality data are maintained by other servers **122** by zip codes or by statistical metropolitan areas. The size of the general area may also be further application dependent. For example, even though the air quality data are available by zip codes, air/asthma application **114** may nevertheless treat all areas with the same m most significant zip code digits as the same general area.

Upon retrieving air quality (and optionally, other asthma related data), air/asthma application **114** generates air/asthma advice for each patient client **102**, based at least in part on the allergen level data received from the patient client **102** for a monitored location and the retrieved air quality data for the surrounding general area of the monitored location. Thus, for the purpose of the present invention, as long as the companion outdoor air quality to be taken into consideration in the generation of air/asthma advice is considered invariant (as in the case of a statistical metropolitan area), a monitored location such as the interior space of the patient client's automobile or boat (when used on a routine "local" basis, as opposed to an exceptional long distance journey) is "substantially stationery", equivalent to that of a "fixed" location, as in the case of the patient's home or office.

For the particular embodiment, patient client database **116** stores medical as well as basic identification information for each of a number of

patient clients **102**. In generating air/asthma advice for each patient client **102**, air/asthma application **114** further takes into consideration the relevant medical information maintained for the patient client **102**. Similarly, what medical information is considered relevant and taken into consideration is also application dependent. That is, in a more sophisticated variation of the embodiment, more medical information may be taken into consideration, and in a less sophisticated variation of the embodiment, less medical information may be taken into consideration. In a most basic alternative embodiment, air/asthma application **114** may simply generate the air/asthma advice without taking into consideration the medical data of a patient client **102**. Additionally, non-medical client data, such as location and construction of "home", proximity to sources of ambient air pollution (e.g. highways, power plants, chemical facilities, and so forth), may also be collected, and taken into consideration by air/asthma advice application **114**.

Upon generating an air/asthma advice response in one of the above described manners, air/asthma advice application **114** provides the generated air/asthma advice response to the patient client **102** through the patient client's air/asthma advice receipt arrangement **106**. The content of the advice response is application dependent, e.g. the response may be an indoor air quality advisory, an outdoor air quality advisory, a weather advisory and/or a natural/man made pollution event advisory. The advice response may be provided in any one of a number of forms, including but not limited to, a beeping signal, a paging message, a voice message, a fax message, an email, and so forth, so long it is consistent with the capability of the air/asthma advice receipt arrangement **106** provided to the particular patient client **102**. Different types of receipt arrangement **106**, and therefore, different advice response forms may be employed for different patient clients **102**. Multiple receipt arrangements **106** may also be provided for one patient client **102**. In alternate embodiments, the air/asthma advice responses may also be provided to the

patient clients' parents, guardians, nurses or doctors, in lieu of or in addition to the patient clients.

Having now described an overview of the present invention, various embodiments of allergen detection arrangement **104** as well as air/asthma advice receipt arrangement **106** will be described in more detail below, along with communication link or links **108**, referencing **Fig. 2a-2b** and **Fig. 3a-3e**. Similarly, one embodiment each of server **112**, air/asthma application **114** and patient client database **116** will be described in more detail below, referencing **Fig. 4-6**. As to remote servers **122**, the examples described above adequately set forth their nature to practice the present invention. It is readily apparent from these examples, communication link or links **118** may be any one of a number of communication medium known in the art, including but not limited to the Public Switching Telephone Network (PSTN), the Integrated Service Digital Network (ISDN), a Frame Relay network, an Asynchronous Transfer Mode (ATM) network, or the Internet, depending on the requirement of remote servers **122** accessed. Accordingly, remote servers **122** and communication link or links **118** will not be further described.

Referring now to **Figures 2a-2b**, wherein two block diagrams illustrating allergen detection arrangement **104** of **Fig. 1** in further detail, in accordance with two embodiments, are shown. For the embodiment of **Fig. 2a**, arrangement **104** includes one or more "basic" allergen data collection units **202** and a companion base station **242**, coupled to each other through communication link or links **232**. Allergen data collection unit **202** includes filtering arrangement **204**, sensor **206**, analog-to-digital (A/D) converter **208**, data buffer **210**, communication interface **212**, and micro-controller **212**, coupled to each other as shown. Base station **242** includes communication interface **244**, data buffer **246**, communication interface **248**, and micro-controller **250**, coupled to each other as shown.

Filtering arrangement **204** (of allergen data collection unit **202**) is used to filter out large allergens in the ambient air that are not relevant to the issue of asthma trigger, allowing only allergens smaller than certain sizes that are relevant to the issue of asthma trigger to pass through. In one embodiment, filter arrangement **204** filters out allergens with sizes 5 micron or larger, allowing only allergens with sizes smaller than 5 micron to pass through. In one embodiment, filter arrangement **204** is a collection of successive filters. In other embodiments, filter arrangement **204** may be a cyclone separator, or a virtual impactor.

Sensor **206** (of allergen data collection unit **202**) monitors and detects the amount of allergens present in the filtered air, and outputs signals representative of the amount detected. In one embodiment, sensor **206** is of the optical type, capable of detecting and outputting signals to denote the amount of allergens (smaller than 5 microns) in the filtered air. An example of such sensor is the GP2U06 High Sensitivity Dust Sensor available from Sharp Electronics Corporation of Camas, WA. Other sensors or sensor modules with similar capability or built along similar principles may also be used.

Analog-to-digital (A/D) converter **208** digitizes the allergen level signals output by sensor **206**, and data buffer **210** stores the digitized allergen data. Communication interface **212** facilitates provision of the buffered allergen data (via communication link or links **262**) to base station **242** for transmission to air/asthma advice server **112**. Micro-controller **214** controls the operation of these elements. A/D converter **208**, data buffer **210**, communication interface **212** and micro-controller **214** are intended to represent a broad range of these elements known in the art. For examples, data buffer **210** may be SRAM, DRAM, and memory of other like kinds, and micro-controller **214** may be 8-bit, 16-bit, or >16-bit micro-controller. Communication interface **212** may be a serial or parallel interface, a serial bus interface, a "harsh environment" wired network controller or a wireless transceiver. Examples of serial bus interfaces are bus interfaces designed for the Universal Serial Bus (USB) as specified by

USB Specification R1.0, January 15, 1996, or the "Firewire" serial bus as specified by IEEE 1394 High Performance Serial Bus. Examples of "harsh environment" network controllers are network controllers designed for the consumer electronics bus as specified by The CEBus Standard EIA-600, for phone line based networking (as AnyPoint™ Home Networking controllers available from Intel Corporation of Santa Clara, CA), or for power line based networking (as controllers available from Intelogis of American Fork, Utah). Examples of wireless transceivers are transceivers designed in accordance with the Draft Specification of Bluetooth: A Global Specification for Wireless Connectivity, promulgated by the Bluetooth Special Interest Group, and wireless network controllers designed in accordance with IEEE 802.11 Wireless LAN Standard.

Communication interface **244** (of base station **242**) facilitates receipt of the collected allergen data (via communication links **232**) from allergen data collection unit or units **202**. Communication interface **244** is an interface of like kind that complements communication interface **212** (of allergen data collection unit **202**). Similar to data buffer **210** (of allergen data collection unit **202**), data buffer **246** (of base station **242**) temporarily stores the received allergen data, and staged them for transmission to geographically removed air/asthma advice server **112**. Communication interface **248** (of base station **242**) facilitates the actual transmission to air/asthma advice server **112**. Likewise, micro-controller **250** controls the operations of these elements. Again, data buffer **246**, communication interface **248**, and micro-controller **250** are intended to represent a broad range of these elements known in the art. Data buffer **246** may be SRAM, DRAM and memory of other like kinds, and micro-controller **250** may be 8-bit, 16-bit or >16-bit micro-controllers. Communication interface **248** may be a modem, an ISDN adapter, a DSL adapter and the like, depending on whether the communication link between base station **242** and air/asthma advice server **112** is a PSTN connection, an ISDN connection or a

Digital Subscriber Line (DSL) connection, and so forth. Other communication interfaces consistent with the communication media may also be used.

As alluded to earlier in the description of communication interface **212** of allergen data collection unit **202**, communication link **262** may be a wired or a wireless communication connection. In the case of a wired communication connection, link **262** may be a serial or a parallel link, a serial bus, as well as a "harsh environment" local area network segment, as set forth above. In the case of a wireless communication link, link **262** may be any one of the example wireless medium set forth above.

In alternate embodiments, base station **242** may be replaced with a computer, properly equipped with the dual communication interfaces. These alternate embodiments are particularly useful in a home or office settings where the required computer already exist, thereby advantageously allowing the patient client to leverage on his/her past equipment investment. Alternatively, in like manner, base station **242** may be replaced with a cell phone. Such alternate arrangement is particularly useful in the above described automobile or boat settings, where the patient client is already equipped with a cell phone, thereby also advantageously allowing the patient client to leverage on his/her past equipment investment.

The embodiment of **Fig. 2b** is a "full" function integrated embodiment of allergen detection arrangement **104**. That is, the data collection unit and the base station transmission unit of **Fig. 2a** have been combined into a single unit, and additional functional units are provided. Thus, similar to the embodiment of **Fig. 2a**, under the embodiment of **Fig. 2b**, arrangement **104** still includes filter arrangement **272**, allergen sensor **274** and A/D converter **276**, performing like functions as described earlier. However, unlike the embodiment of **Fig. 2a**, a single communication interface **278**, capable of directly facilitating provision of the buffered allergen data to the geographically removed air/asthma advice server, as opposed to the dual communicative

interfaces and base station approach, is used instead. In other words, communication interface **278** is analogous to the communication interface of the base station of **Fig. 2a**, and the communication interface of the “basic” allergen data collection unit has been eliminated.

Additionally, arrangement **104** is further provided with peak flow meter **280**, a spirometer **282**, a thermometer **284**, a humidity meter **286**, and chemical sensors **288** to measure various asthma related metrics. Peak flow meter **280** measures peak expiratory flow rate of a patient client, whereas spirometer **282** measures the forced expiratory volume and other lung function metrics of a patient client. Thermometer **284** measures the temperature of the ambient air and humidity meter **286** measures the humidity of the ambient air. Chemical sensors **288** measure various gas levels, e.g. carbon monoxide, ozone, nitrogen dioxide, sulfur dioxide, and so forth. These elements are known in the art. Arrangement **104** also includes display and input interface **290** to interact with the patient client, to facilitate provisions of inputs from, and feedback to the patient client. Display and input interface **290** may be any end-user input/output device known in the art. Larger memory **292** and more powerful microprocessor **294** are provided to buffer allergen and other asthma related (like peak expiratory flow rate) data, and to control the operation of the various elements. For the illustrated embodiment, the various elements are coupled to each other through bus **296**, which may be one or multiple buses bridged together. Bus **296** may be any one of a number of system or peripheral buses known in the art, such as the I²C bus, the ISA bus, the EISA bus, and the like.

Referring now **Figures 3a-3e**, wherein a number of example air/asthma advice receipt arrangements, suitable for use with the allergen detection arrangements of **Fig. 2a-2b**, in accordance with a number of embodiments, are shown. **Figure 3a** illustrates a conventional beeper known in the art. Under this embodiment, patient client **102** is provided with beeper **302**, which in turn is employed by air/asthma advice server **112** to deliver a beeping signal to alert

patient client **102** of an undesirable air/asthma condition. **Figure 3b** illustrates a conventional pager known in the art. Under this embodiment, patient client **102** is provided with pager **304**, which in turn is employed by air/asthma advice server **112** to page patient client **102** to call a particular telephone number for air or asthma advice, in view of an undesirable air/asthma condition.

Figure 3c illustrates a conventional PSTN or cellular telephone known in the art. Under this embodiment, patient client **102** is provided with telephone **306**, which in turn is employed by air/asthma advice server **112** to deliver a verbal advice to patient client **102** in view of an undesirable air/asthma condition. If a cell phone is employed in lieu of base station **242** for allergen detection arrangement **104** (under the embodiment of **Fig. 2a**), phone **306** may be the same phone. Air/asthma advice server **112** may wait till phone **306** is not in use (e.g. not providing allergen data) before calling patient client **102** to provide the verbal advice.

Figure 3d illustrates a conventional fax machine known in the art. Under this embodiment, patient client **102** is provided with fax machine **310**, which in turn is employed by air/asthma advice server **112** to deliver a written advice to patient client **102** in view of an undesirable air/asthma condition.

Figure 3e illustrates a conventional computer (equipped with communication and email capability) known in the art. Under this embodiment, patient client **102** is provided with computer **312**, which in turn is employed by air/asthma advice server **112** to deliver an electronic written advice to patient client **102** in view of an undesirable air/asthma condition. If a computer is employed in lieu of base station **242** for allergen detection arrangement **104** (under the embodiment of **Fig. 2a**), computer **310** may be the same computer. For this embodiment, communication links **108** and **110** may be the same communication link.

Referring now to **Figure 4**, wherein a block diagram illustrating an example server suitable for use as air/asthma advice server **112** of **Fig. 1**, in

accordance with one embodiment, is shown. As illustrated, server **400** includes a number of processors **402** and system memory **404** coupled to each other via system bus **406**. System bus **406** is intended to represent a single bus implementation as well as a multi-bus implementation (where the buses are bridged together). Coupled to system bus **406** are non-volatile mass storage **408**, such as hard disks, floppy disk, and so forth, input/output devices **410**, such as keyboard, displays, and so forth, and communication interfaces **412**, such as modem, ISDN adapters, DSL adapters, T1 DSU/CSU, cellular transceivers, satellite transceivers, Ethernet controllers, and so forth. For the illustrated embodiment, server **400** also includes voice response unit **414**, which is also coupled to system bus **406**. In alternate embodiments, server **400** may be a uni-processor system instead.

Each of these elements perform its conventional functions known in the art, i.e. processors **402** are used to execute programming instructions, system memory **404** and non-volatile mass storage **408** are used to store working and permanent copies of the programming instructions and data, and so forth. In particular, system memory **404** and non-volatile mass storage **408** are employed to store a working copy and a permanent copy of the programming instructions implementing air/asthma advice application **114** and patient client database **116**. The constitution of elements **402-414** are well known, and accordingly will not be further described.

Referring now to **Figure 5**, wherein a block diagram illustrating air/asthma advice application **114** of **Fig. 1** in further detail, in accordance with one embodiment, is shown. As illustrated, air/asthma advice application **114** includes registration module **502**, air/asthma advice response generation module **504**, and air/asthma advice delivery module **506**. For the illustrated embodiment, air/asthma advice application **114** further includes aggregate statistical reporting module **508**. These modules **502-508** are operationally "coupled" to each other and patient client database **116** as shown.

Registration module **502** is used to enroll and register patient client **102**. In response to a registration request, registration module **502** creates a patient client record, along with the proper patient client information, to be described more fully below, in patient client database **116**. For the illustrated embodiment, registration module **502** supports direct on-line registration by the patient client or the patient client's representative (in particular, through the Internet), as well as registration by an agent of the air/asthma advice server **112**. Examples of the patient client's representative are the patient client's doctor, nurse, parent, guardian, and so forth, as described earlier.

Air/asthma advice generation module **504** is used to generate air/asthma advice for the patient clients, taking into consideration at least collected allergen data provided by the patient clients, and the air quality and related data for the surrounding areas of the allergen data collection locations. As described earlier, in response to the receipt of allergen data of a monitored location, generation module **504** retrieves air quality and related data from remote servers **122**, and produces the air/asthma advice as set forth earlier.

For the illustrated embodiment, generation module **504** stores the advice generated for a patient client in an advice portion of the patient client's record in patient client database **116**. Additionally, generation module **504** schedules the stored advice for delivery by delivery module **506**. Scheduling is made by creating a delivery entry in a delivery job queue (not shown). Alternate approaches may also be employed.

For the illustrated embodiment, an identifier of the monitored location (e.g. a zip code, an identifier of a statistical metropolitan area, a telephone number area code, a global positioning coordinate, and so forth) may be dynamically provided along with the collected allergen data. However, an identifier of the patient client is always directly or indirectly provided (e.g. through a phone number or a unique network address of the patient client). If the identifier of the monitored location is not dynamically provided along with the collected allergen data, generation module **504** assumes the monitored

location is a defaulted location (e.g. the patient client's home) previously identified and stored in patient client database **116**, and retrieves the pre-stored default location identifier for the patient client accordingly.

For the illustrated embodiment, generation module **504** caches local copies for the air quality and related data for various surrounding areas. Accordingly, generation module **504** retrieves the air quality and related data for a surrounding area from the local cache, if the data are available locally and valid. Various application dependent validity policies, such as "not older than 7 days" or "not older than 24 hours" may be employed. That is, cache data are invalidated or considered to be invalid, once their "shelf lives" have exceeded the validity policy limits.

For the illustrated embodiment, generation module **504** also takes into consideration medical history of a patient client (including various allergen trigger thresholds), and employs artificial intelligence (AI) to generate the air/asthma advice responses. The precise policies to be employed for the AI reasoning portion of generation module **504** is application dependent. It may vary from a small set of simple rules to a large complex collection of interdependent rules.

Air/asthma advice delivery module **506** is used to make the actual delivery of the generated air/asthma advice to the patient clients (or their representatives, i.e. doctors, nurses, parents, guardians and so forth). As described earlier, the advice may be delivered in a variety of forms, beeping signals, pager messages, and so forth, and the patient clients may be equipped with different advice receipt arrangements. For the illustrated embodiment, delivery module **506** is equipped to support delivery in a wide range of forms, including in particular a beeping signal, a pager message, a voice message, a fax message, and an email. The preferred delivery form or forms of a patient client (and/or the representative) is pre-stored in patient client database **116**. In response to the scheduling of a delivery job, delivery

module **506** ascertains the appropriate delivery form or forms for the advice, and makes the delivery accordingly.

In addition to the "push" model for delivering generated advice, delivery module **506** also supports a "pull" model for delivering generated advice. That is, delivery module **506** also "delivers" the generated advice to the patient client or his/her representative (e.g. doctor, nurse and so forth) in response to their queries (in particular, through the Internet).

Aggregated statistical reporting module **508** is used to compile and report on various advice related statistics. Examples of these aggregated statistics include cumulative exposures to indoor or outdoor allergens, correlation between individual or cumulative exposure data and lung function measurements, minimum, maximum, mean and standard deviation of exposure and lung function data by single and multiple unit dwellings and by geographical areas, multiple dwellings aggregated by common "medical" as well as non-medical characteristics, and so forth. The compiled statistics may be provided to interested third parties as well as operator of air/asthma advice server **112**. Examples of interested third parties are educational and research institutions, pharmaceutical and medical device manufacturers, distributors and retailers, and marketing research organizations. For the illustrated embodiment, reporting module **508** supports batch delivery of the compiled statistics as well as on-line inquiry of the compiled statistics (in particular, through the Internet).

Modules **502-508** may be implemented in a variety of programming languages known in the art, including but not limited to, C, C++, Hypertext Markup Language (HTML), Java, JavaScript, and so forth.

Referring now to **Figure 6**, wherein a block diagram illustrating patient client database **116** of **Fig. 1** in further detail, in accordance with one embodiment, is shown. As illustrated, patient client database **116** includes various patient client records **602**. Each patient client record **602** includes

patient client identifier **604** identifying the patient client. In addition, each record **602** also includes basic information **606** about the patient client, medical related information **608** of the patient client, allergen data collected **610**, and advice generated/delivered **612**. Examples of basic information **604** include the patient client's address, phone number, doctor's name, address and phone number, pharmacist's name address and phone number, identifier and characteristics of the defaulted monitored location, password for accessing the patient client's information, and so forth. Where applicable, it may also include parent or guardian information. Examples of medical related information **606** include the patient client's birthday, age, allergens allergic to, trigger thresholds for various allergens and related matters, medication currently taking, and so forth. Allergen data collected **610** includes related data such as temperature, humidity, level of various gases in the ambient air, as well as in some embodiments, the patient clients' peak expiratory flow rate, and forced expiratory volume. Air/asthma advice generated/delivered **612** includes the advice, and the date and time the advice are generated and delivered, as well as to whom and in what form the advice were delivered.

Referring now to **Figure 7**, wherein a block diagram summarizing an air/asthma advice method of the present invention, in accordance with one embodiment, is shown. As illustrated, at **702**, a patient client is registered or enrolled with an operator of the air/asthma advice server described earlier, resulting in the creation of a patient client record in the patient client database for the patient client. The registration may be made by the patient client or a representative (doctor, nurse, and so forth) on behalf of the patient client. The registration may be made directly on-line or by an agent of the operator.

At **704**, a registered patient client, using an allergen detection arrangement, provides collected allergen data for a monitored location to the air/asthma advice server. The monitored location may be a default location, or a temporal location (dynamically identified for the air/asthma advice server). At

706, air/asthma advice server retrieves air quality and related data for a general area surrounding the monitored location. The data are either retrieved from local cached copies or directly from remote servers (operated by various public or private institutions). At **708**, air/asthma advice server generates air/asthma advice for the patient client based at least on the allergen data provided and the air quality and related data retrieved. In one embodiment, the air/asthma advice is generated based also on the medical history of the patient client.

At **710**, performed immediately or in due course, the air/asthma advice server delivers the air/asthma advice for the patient client. The delivery may be made to the patient client and/or his/her representative, in one or more of a number of forms, as described earlier.

Epilogue

Various embodiments for methods and apparatuses for detecting allergen and generating/providing air/asthma advice for patient clients have been described. Those skilled in the art will recognize that the present invention is not limited by the embodiments and their detail described, instead, the present invention can be practiced with modifications and alterations within the spirit and scope of the appended claims. The description is thus to be regarded as illustrative instead of restrictive on the present invention.

CLAIMS

What is claimed is:

1. A method comprising:
receiving allergen data collected at a location;
retrieving air quality data for a surrounding area of the location; and
generating an allergen advice response based at least in part on the received allergen data and the retrieved air quality data.
2. The method of claim 1, wherein said allergen data comprises data for allergen with sizes smaller than 5 micron.
3. The method of claim 1, wherein said air quality data comprises data selected from a group consisting of ozone, oxides of nitrogen, oxides of sulphur, photochemical smog, humidity, temperature, barometric air pressure, pollen level, occurrence of sandstorm, occurrence of tornado, occurrence of forest fire, occurrence of agricultural burning.
4. The method of claim 1, wherein said retrieving comprises retrieving said air quality data from a remote server through a data connection, said remote server is a server maintained by an entity selected from a group consisting of a government agency, a hospital, a university, a research institution, a news reporting organization, and a commercial air quality reporting service.
5. The method of claim 1, wherein said allergen advice response comprises a response selected from a group consisting of an indoor air quality advisory, an outdoor air quality advisory, a weather advisory, and a natural/mad-made pollution event advisory.
6. The method of claim 1, wherein the method further comprises delivering the generated allergen advice response to a recipient selected from a group consisting of a patient, a medical physician, a nurse, a pharmacist, a parent and a guardian, and in a form selected from a group consisting of beeping

signal, a pager message, a voice message, a faxed report, and an e-mail message.

7. The method of claim 1, wherein said receiving further comprises receiving additional data selected from a group of consisting of lung function data of a patient, ambient temperature of the location, humidity at the location, and concentration of a gas at the location, and said allergen advice response is generated based also in part on said received additional data.

8. The method of claim 1, wherein said allergen advice response is generated based also in part on allergen triggering threshold(s) provided by one selected from a group consisting of the patient, a medical physician and a nurse.

9. The method of claim 1, wherein said retrieving further comprises retrieving weather data of the surrounding area from a remote server of a weather monitoring and reporting service, and said allergen advice response is generated based also in part on said retrieved weather data.

10. The method of claim 1, wherein the method further comprises compiling aggregated statistical data on said generation of allergen advice response, and providing said compiled aggregated statistical data to a recipient selected from a medical research organization, a product marketing organization, a product manufacturer, a product distributor, and a product retailer.

11. An apparatus, comprising:
a processor
at least one communication interface coupled to the processor; and
a storage medium coupled to processor and having stored therein a first, a second, and a third plurality of programming instructions to be executed by the processor to receive allergen data collected at a location, to retrieve air quality data for a surrounding area of the location, and to generate an allergen advice response based at least in part on the received allergen data and the retrieved air quality data, respectively.

12. The apparatus of claim 11, wherein said storage medium further having pre-stored therein said air quality data.
13. The apparatus of claim 11, wherein said storage medium further having stored therein a fourth plurality of programming instructions to be executed by the processor to deliver the generated allergen advice response to a recipient in a form selected from a group consisting of a beeping signal, a pager message, a voice message, a faxed report, and an e-mail message.
14. The apparatus of claim 11, wherein said first plurality of programming instructions are also to be executed by the processor to receive additional data selected from a group of consisting of lung function data of a patient, ambient temperature of the location, humidity at the location, and concentration of a gas at the location, and said third plurality of programming instructions in generating said allergen advice response further base said generation on said received additional data.
15. The apparatus of claim 11, wherein said second plurality of programming instructions are also to be executed by the processor to retrieve weather data of the surrounding area, and said third plurality of programming instructions in generating said allergen advice response further base said generation on said retrieved weather data.
16. The apparatus of claim 11, wherein said storage medium further having stored therein a fourth plurality of programming instructions to be executed by the processor to compile aggregated statistical data on said generation of allergen advice response.
17. An allergen data collection device comprising:
 - a sensor to detect presence of allergen with sizes smaller than 5 micron in an air stream, and to output signals indicative of the amount of allergen present, if any, at different points in time; and
 - a communication interface coupled to the sensor to facilitate forwarding of data values digitized from the output signals to a proximally located digital

apparatus for transmission to a geographically removed air/asthma advice server.

18. The allergen data collection device of claim 17, wherein the device further comprises an analog-to-digital (A/D) converter coupled to the sensor to receive and digitize said output signals into said data values.

19. The allergen data collection device of claim 18, wherein the device further comprises a filter arrangement disposed in front of an input end of the sensor to filter out allergens with sizes 5 micron and larger from the air stream.

20. The allergen data collection device of claim 17, wherein the communication interface is a networking interface selected from a group consisting of a Bluetooth based wireless networking interface, an IEEE 802.11 standard based networking interface, a power-line based networking interface, and a phone wire based networking interface.

21. An asthma management device comprising:

a sensor to detect presence of allergen with sizes smaller than 5 micron in an air stream, and to output signals indicative of the amount of allergen present, if any, at different points in time;

a lung function meter to measure a lung function metric of a user; and
a communication interface coupled to the sensor sub-assembly to facilitate forwarding of allergen data values digitized from said output signals and said measured lung function metrics to a geographically removed air/asthma advice server.

22. The asthma management device of claim 21, wherein the lung function meter is a peak flow meter to measure peak expiratory flow rate of the user, and the communication interface further facilitates forwarding of the measured peak expiratory flow rate to the geographically removed air/asthma advice server.

23. The asthma management device of claim 21, wherein the lung function meter is a personal spirometer to measure forced expiratory volume of the user, and the communication interface further facilitates forwarding of the

measured forced expiratory volume to the geographically removed air/asthma advice server.

24. The asthma management device of claim 21, wherein the device further comprises a thermometer to measure ambient temperature, and the communication interface further facilitates forwarding of the measured temperature to the geographically removed air/asthma advice server.

25. The asthma management device of claim 21, wherein the device further comprises a humidity meter to measure ambient humidity, and the communication interface further facilitates forwarding of the measured humidity to the geographically removed air/asthma advice server.

26. The asthma management device of claim 21, wherein the device further comprises one or more gas detection sensors to detect and measure presence of one or more gases selected from a group consisting of carbon monoxide, ozone, nitrogen oxide (NO_x), and sulfur oxide (SO_x), and the communication interface further facilitates forwarding of the measured amount of the one or more gases to the geographically removed air/asthma advice server.

27. The asthma management device of claim 21, wherein the communication interface is an interface selected from a group consisting of a Public Switching Telephone Network (PSTN) interface, an Integrated Service Digital Network (ISDN) interface, and a digital subscriber line (DSL) interface.

28. The asthma management device of claim 21, wherein the device further comprises an end-user interface to provide facilitate provision of air/asthma advice to a patient by the geographical removed air/asthma advice server through the communication interface, where the air/asthma advice is generated by the geographically removed air/asthma advice server based at least in part on the allergen data provided to the air/asthma advice server, and air quality data of an area surrounding a disposition location of the asthma management device, the air quality data being maintained/obtained by the air/asthma advice server.

29. The asthma management device of claim 21, wherein the device further comprises an A/D converter coupled to the sensor to digitize the output signals as said allergen data values, and memory coupled to the A/D converter and the lung function meter to store the digitized allergen data values and the measured lung function metrics of the user.

30. A personal asthma management device comprising:

- a sensor to detect presence of allergen with sizes smaller than 5 micron in an air stream, and to output signals indicative of the amount of allergen present, if any, at different points in time;

- at least one sensor to measure at least one metric for ambient air; and

- a communication interface coupled to the sensor sub-assembly to facilitate forwarding of allergen data values digitized from the output signals and said at least one measured ambient air metric to a geographically removed air/asthma advice server.

31. The asthma management device of claim 30, wherein the at least one sensor comprises at least one of a thermometer to measure ambient temperature and a humidity meter to measure ambient humidity, and the communication interface further facilitates forwarding of at least one of the measured temperature and the measured humidity to the geographically removed air/asthma advice server.

32. The asthma management device of claim 30, wherein the at least one sensor comprises one or more gas detection sensors to detect and measure presence of one or more gases selected from a group consisting of carbon monoxide, ozone, nitrogen oxide (NO_x), and sulfur oxide (SO_x), and the communication interface further facilitates forwarding of the measured amount of the one or more gases to the geographically removed air/asthma advice server.

33. The personal asthma management device of claim 30, wherein the communication interface is an interface selected from a group consisting of a

Public Switching Telephone Network (PSTN) interface, an Integrated Service Digital Network (ISDN) interface, and a digital subscriber line (DSL) interface.

34. The asthma management device of claim 30, wherein the device further comprises an A/D converter coupled to the sensor to digitize the output signals as said allergen data values, and memory coupled to the A/D converter and the spirometer to store the digitized allergen data values and the measured forced expiratory volume of the user.

35. The asthma management device of claim 30, wherein the device further comprises an end-user interface to facilitate provision of air/asthma advice to a patient by the geographical removed air/asthma advice server through the communication interface, where the air/asthma advice is generated by the geographically removed air/asthma advice server based at least in part on the allergen data provided to the air/asthma advice server, and air quality data of an area surrounding a disposition location of the asthma management device, the air quality data being maintained/obtained by the air/asthma advice server.

1/7




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E

5/7




FIG. 4


114

FIG. 5




FIG. 6

7/7




FIG. 7

THIS PAGE BLANK (USPTO)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 March 2001 (08.03.2001)

PCT

(10) International Publication Number
WO 01/16854 A3

(51) International Patent Classification⁷: G06F 19/00

(21) International Application Number: PCT/US00/20356

(22) International Filing Date: 25 July 2000 (25.07.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

09/387,041	31 August 1999 (31.08.1999)	US
09/387,043	31 August 1999 (31.08.1999)	US

(71) Applicant: AIR ADVICE.COM [US/US]; 1727 S.E. 43rd Street, Portland, OR 97215 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report


(72) Inventor: SKARDON, John, N.; 14413 N.E. 26th Avenue, Vancouver, WA 98686 (US).

(88) Date of publication of the international search report:
20 September 2001

(74) Agents: AU YEUNG, Aloysius, T., C. et al.; Columbia IP Law Group LLC, 4900 SW Meadows Road, Suite 109, Lake Oswego, OR 97035 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ALLERGEN DETECTION AND AIR/ASTHMA ADVICE PROVISION



(57) Abstract: A novel air/asthma advice method and apparatus for providing air/asthma advice to an asthma patient, taking into consideration indoor allergen as well as outdoor air quality conditions, is disclosed. Allergen data (preferably for allergen with sizes smaller than 5 microns) for an indoor location (where the asthma patient is situated) are collected, and provided to a geographically removed air/asthma advice server. The server, in turn, retrieves air quality data for a surrounding outdoor area of the indoor location (from either a private or an independent source), and generates an allergen advice response for the asthma patient. The air/asthma advice is generated based at least in part on the received allergen data and the retrieved air quality data. The air/asthma advice may be delivered to the asthma patient in any one of a number of forms (a beeping alert, a pager, fax, email or voice message, and so forth). Various other alterations and modifications under different embodiments are also disclosed.

WO 01/16854 A3

INTERNATIONAL SEARCH REPORT

In: International Application No
PCT/US 00/20356

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G06F19/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
E	WO 00 65996 A (WIKBERG HARRI ; HEINONEN PEKKA (FI); NOKIA CORP (FI); BLANTS LIOUDM) 9 November 2000 (2000-11-09) abstract; claims 1-34 ---	1-35
P, X	WO 99 46921 A (NOKIA MOBILE PHONES LTD ; OKKONEN HARRI (FI); HEINONEN PEKKA (FI)) 16 September 1999 (1999-09-16) abstract; claims 1-11 page 1, paragraph 3 ---	1-35
X	US 5 827 180 A (GOODMAN DAVID F) 27 October 1998 (1998-10-27) abstract; claim 1; figures 10A-B column 11, paragraph 1 --- -/--	1-35

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

7 March 2001

Date of mailing of the international search report

14/03/2001

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Fillooy García, E

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 00/20356

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 704 366 A (SANDERS MATTHEW H ET AL) 6 January 1998 (1998-01-06) abstract; claim 1 ---	1-35
Y	US 5 892 690 A (BOATMAN JOEY F ET AL) 6 April 1999 (1999-04-06) abstract; claims 1-20 column 1, paragraph 1 - paragraph 5 -----	1-35

INTERNATIONAL SEARCH REPORT

Information on patent family members

In. tional Application No

PCT/US 00/20356

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0065996	A	09-11-2000	AU 3970000 A	17-11-2000
WO 9946921	A	16-09-1999	FI 980538 A	10-09-1999
			AU 2426999 A	27-09-1999
			EP 1062799 A	27-12-2000
US 5827180	A	27-10-1998	NONE	
US 5704366	A	06-01-1998	AU 703391 B	25-03-1999
			AU 2646395 A	18-12-1995
			CA 2190283 A	30-11-1995
			DE 69519166 D	23-11-2000
			EP 0765507 A	02-04-1997
			ES 2151067 T	16-12-2000
			JP 10500598 T	20-01-1998
			WO 9532480 A	30-11-1995
			US 5626144 A	06-05-1997
			US 5549117 A	27-08-1996
			US 5732709 A	31-03-1998
US 5892690	A	06-04-1999	AU 6693398 A	29-09-1998
			WO 9840859 A	17-09-1998